



FAST PRINTS USA
ALL YOUR PRINTING NEEDS

SPEC SHEET
PRODUCT SPECIFICATIONS



3M™ **IJ-35C**

4 mil Pressure-Sensitive Adhesive Vinyl
3M Comply™ Air Release Technology

COMMON USES

Windows, Walls, Promotions, Retail, Event Graphics & More

ENVIRONMENT

Indoor & Outdoor

SIZE OPTIONS

Custom Size

PRINT SIDES

Single-Sided

FINISHING OPTIONS

Contour Cut

Gloss, Matte or No Laminate



3M COMPLY™ AIR RELEASE

Fast, easy, bubble-free installations every time.



INDOOR & OUTDOOR DURABLE

Rated -59° to +192°F for lasting performance.



CUSTOM & CONTOUR CUT

Any size, any shape — gloss, matte or no laminate.



Technical Data Sheet

PROPERTIES

Pressure-sensitive adhesive with 3M Comply™ Adhesive for fast, easy, bubble-free installations.

PHYSICAL CHARACTERISTICS

Material	Vinyl	Adhesive Type	Pressure-Sensitive
Color	White Opaque	Adhesive Color	Gray
Film Thickness (no adhesive)	3.2 mil (0.081 mm)	Liner	Polycoated Paper
Film Thickness (with adhesive)	4.0 mil (0.102 mm)	Print Sides	Single-Sided

APPLICATION CHARACTERISTICS

Surface Type	Smooth, flat & simple curves	Application Method	Dry
Substrate Type	Metal, rigid plastic, painted	Application Temp.	40° to 100°F (4° to 38°C)
Graphic Removal	Permanent	Exposure Temp.	-59° to +192°F (-50° to +90°C)

EXPOSURE TYPES

U.S. Vertical Exposure	Graphic face is +/- 10° from vertical
------------------------	---------------------------------------

RECOMMENDED APPLICATION

Apply to clean, smooth, flat or simple-curved surfaces within the rated temperature range for best results. Finished graphics are rated for permanent, durable indoor & outdoor performance.

Technical specifications reflect manufacturer (3M) data for the IJ-35C film and are provided for reference. 3M™, IJ-35C and Comply™ are trademarks of 3M. Fast Prints USA prints on this substrate and is not affiliated with 3M. Values are nominal; verify suitability for your application before production. For a quote or material questions, contact Fast Prints USA.