



Boot Prints

Heavy-Duty Outdoor Floor Vinyl

Anti-Slip · Extreme Adhesion · Long-Term

COMMON USES

Outdoor, Long-Term — Concrete, Asphalt, Brick & Rough Surfaces

MATERIAL

Anti-Slip Adhesive Floor Vinyl

ENVIRONMENT

Outdoor

OPTIONS

Custom Size, Contour Cut

ADHESION

Extreme / Aggressive

PRINT SIDES

Single-Sided



EXTREME ADHESION

Aggressive adhesive grips rough concrete, asphalt and brick.



ANTI-SLIP SURFACE

Textured laminate built for foot traffic outdoors.



LONG-TERM OUTDOOR

Engineered to hold on demanding exterior surfaces.

Surface, Application & Care

PRODUCT

Material	Anti-slip outdoor floor vinyl	Finish	Anti-slip textured laminate
Adhesion	Extreme / aggressive	Environment	Outdoor
Print Sides	Single-sided	Options	Custom size, contour cut

SURFACE REQUIREMENTS

- Designed for rough exterior surfaces — concrete, asphalt, brick and pavers
- Surface must be swept clean, dry and free of loose debris, oil and curing compounds
- Allow new concrete to fully cure (about 28 days) before application

APPLICATION

- Apply above 50 °F to a dry surface
- Press the full graphic down firmly and roll from the center outward to seat the adhesive into the texture
- The aggressive adhesive is meant for long-term placement and is not designed for clean repositioning

CARE

- Sweep or rinse as part of normal cleaning; avoid aiming a pressure washer directly at the edges
- Replace the graphic if the anti-slip surface wears down with heavy traffic

Surface texture, traffic level and weather affect the life of any floor graphic. This sheet describes application and care; it does not state a rated slip coefficient or durability period.