



HD BANNER

Stunningly Vibrant, Premium Vinyl Scrim

Available in 13, 15 & 18 oz Weights

COMMON USES

Sports, Events, Retail & More

LONGEVITY

Short & Medium-Term

PRINT SIDES

Single-Sided

Single / Double-Sided (18oz Only)

OTHER OPTIONS

Smooth, Heat-Welded Edges

Grommets, Pole Pockets, Rope or Wind Slits

ENVIRONMENT

Indoor & Outdoor

SIZE OPTIONS

Custom Size



THREE WEIGHTS

13, 15 & 18 oz premium PVC vinyl scrim.



FINISHING BUILT IN

Heat-welded edges, grommets & pole pockets.



FLAME-RESISTANT

NFPA701 rated for events & venues.

Technical Data Sheet

13 OZ HD BANNER

Base Fabric (DIN 60001)	Polyester	Type of Coating	PVC
Total Weight	440 g/m ² 13 oz	Flame Resistance	NFPA701, B1
Tensile (ISO 13934-1)	1303 × 965 N/5cm 148.8 × 110.2 lbs/in	Tear (ISO 13937-2)	70 × 60 N 15.7 × 13.5 lbs
Elongation (ISO 13934-1)	21 × 28%		

15 OZ HD BANNER

Base Fabric	100% Polyester	Total Weight	~510 g/m ² 15 oz
Type of Coating	PVC	Thickness	~0.38 mm 15 mil
Tensile (ISO 1421-1)	2000/1600 N/5cm 456/365 lbs/2in	Welding Adhesion	45 N/5cm 10 lbs/2in
Tear (DIN 53363)	250/200 N 56/45 lbs	Flame Retardancy (NFPA701)	Pass

18 OZ HD BANNER

Base Fabric	100% Polyester	Total Weight	~610 g/m ² 18 oz
Type of Coating	PVC	Thickness	~0.43 mm 16.8 mil
Tensile (ISO 1421-1)	2100/1800 N/5cm 472/405 lbs/2in	Tear (DIN 53363)	360/310 N 81/70 lbs
Flame Retardancy (NFPA701)	Pass		

18 OZ HD BANNER (DOUBLE-SIDED)

Total Weight	610 g/m ² 18 oz/yd ²	RF Weldable / Heat Sealable	Yes
Tensile (DIN 53354)	2420 × 2058 N/5cm 276 × 235 lbs/in	Fungus Resistant (ASTM G21)	Yes
Tear (DIN 53363)	294 × 245 N 34 × 28 lbs	Low Temp (No Crack)	-30°C -22°F
Flame Resistance	NFPA-701, B1, Title 19, CSFM		

ROPE

Material	Nylon	Line Weight	500 lb Test
Color	Black	Tensile Strength	500 lbs