



MESH

8 oz Coated Polyester
37% Air-Flow Perforation

COMMON USES

Construction, Sponsorships, Events & Outdoor Applications

ENVIRONMENT

Indoor & Outdoor

SIZE OPTIONS

Custom Size

PRINT SIDES

Single-Sided

OPTIONS

Heat-Welded Edges, Grommets
Pole Pockets, Rope & Webbing



37% AIR-FLOW

Wind-permeable for fences & large outdoor spans.



HEAVY-DUTY FINISHING

Heat-welded edges, grommets & pole pockets.



FLAME & FUNGUS RESISTANT

NFPA701 rated, treated coated polyester.

Technical Data Sheet

PROPERTIES

Support Cloth (DIN 60001)	Polyester
Yarn (DIN 53830)	1100 × 1100 dtex 1000 × 1000 denier
Tensile (ASTM D751)	1400 × 1400 N/5cm 160 × 160 lbs/in
Flame Resistance	NFPA701, Title 19, CSM, ASTM E84
RF Weldable / Heat Sealable	Yes
Fungus Resistant (ASTM G21)	Treated

Type of Coating	PVC
Total Weight (ISO 2286-2)	280 g/m ² 8 oz/yd ²
Tear (ASTM D4830)	300 × 300 N/5cm 34 × 34 lbs/in
Low Temp (No Crack, ISO 1876)	-30°C -22°F
Air Permeability @200 Pa (ISO 9237)	2650 mm/sec

ROPE

Material	Nylon
Color	Black

Line Weight	500 lb Test
Tensile Strength	500 lbs